Princess Nourah Bint Abdulrahman University
College of Engineering

Autonomous Plasma-Based Metasurface for Adaptive Satellite Jamming Mitigation

Ghaida Alfahad, Rana Alhatlani, Dana Alotaibi, Jory Almutarrid, Sadeem Almass, Norah Alsowyeh, Renad Almohammadi, Yazan Allawi
Department of Electrical Engineering, College of Engineering, Princess Nourah bint Abdulrahman University, P.O. Box 84428, Riyadh 11671, Saudi Arabia

Abstract

This project presents an innovative approach to mitigating **Radio Frequency Interference (RFI)** in **Low Earth Orbit (LEO)** satellite communications. The core concept relies on the **ionization of noble gases** to transform them into a protective insulating plasma shield, forming a **reconfigurable Electronic Protection (EP) system** through an active metasurface. The study addresses the critical objective of creating a dynamic electromagnetic barrier that can transition from a transparent dielectric state to a reflective conductive state upon ionization. By leveraging the **Drude material model**, the research mathematically demonstrates that precisely increasing electron density (n_e) directly enhances the shielding effectiveness. Simulation data further validates these findings, showing shielding effectiveness levels directly correlated to gas atom density. The project's key findings prove that this software-defined approach can achieve a theoretical Shielding Effectiveness (SE) exceeding 80 dB, providing a robust and agile solution for real-time interference mitigation. The proposed framework is validated through a closed-loop control system that integrates real-time detection with a visual emulation of the plasma activation process, bridging the gap between theoretical electromagnetic modeling and practical system responsiveness.

Introduction

The reliability of modern **Satellite Communication (SATCOM)** is increasingly threatened by the evolution of Electronic Warfare, specifically **high-intensity jamming** that disrupts critical data links. Traditional electronic protection methods rely on static shielding, which often suffers from excessive weight and a lack of operational flexibility, as they permanently block both interference and desired signals. To overcome these challenges, this research proposes an active solution utilizing **ionized neon gas (plasma)** filaments that exhibit frequency-dependent permittivity. This system is theoretically grounded in the electromagnetic properties of plasma, specifically its frequency-dependent permittivity described by the Drude model. When the plasma frequency exceeds the incident wave frequency, the ionized gas behaves as a **reflective medium**, effectively shielding the antenna, analogous to how a conductive metal surface reflects electromagnetic waves below its plasma frequency. By integrating advanced electromagnetic theory with real-time **software-defined activation**, this project demonstrates a lightweight and adaptive metasurface capable of providing high-performance protection and significant shielding efficiency for next-generation aerospace electronic systems.




Figure 1. Electromagnetic Interaction in Plasma Shielding. **Shielding vs. Transparency States.**

System Model / Methodology

The methodology of this research follows a **closed-loop control framework** that integrates mathematical modeling with real-time software execution. The system architecture is divided into three functional layers: **Detection, Logic, and Actuation.** In the Detection layer, an ESP32 microcontroller monitors signal parameters; if a jamming-induced drop in SNR is identified, the Logic layer processes this data using a MATLAB-based Digital Twin. This software component utilizes the Drude Model to calculate the specific **electron density (n_e)** and **attenuation constant (α)** required to neutralize the interference. Finally, the Actuation layer triggers the plasma metasurface emulated in this study via a high-voltage neon-flex grid, to physically demonstrate the transition to a shielding state.

Figure 2. Closed Loop Control Framework

To bridge theoretical plasma physics with experimental demonstration, an optical proof-of-concept is implemented. An LED varies its brightness according to the calculated electron density (n_e), serving as a visual analogy of plasma activation. Quantitative validation remains strictly derived from the neon-based Drude model, with Shielding Effectiveness (SE) evaluated as a function of n_e and frequency.

Proposed Solution / Main Idea

The proposed solution introduces an **Autonomous Plasma-Based Metasurface** designed as a dynamic layer of protection for satellite antennas. Unlike traditional static shields, this system functions as a Software-Defined Barrier that remains transparent under normal conditions and becomes electromagnetically reflective upon detecting interference.

Core Mechanism:

- **Active Ionization:** Utilizing high-voltage excitation to transform noble gas (Neon) filaments into a plasma state.
- **Dynamic Reflectivity:** By modulating electron density (n_e), the system shifts the material's permittivity to a negative value, creating a "Blackout Zone" for incident jamming waves.
- **Smart Feedback Loop:** A real-time control system that autonomously triggers the shield based on Signal-to-Noise Ratio (SNR) degradation.
- **Key Innovation:** This approach provides a lightweight, frequency-adaptive, and energy-efficient defense mechanism that ensures signal integrity without the permanent signal loss associated with traditional shielding materials.




Chart 1. Effect of Ionization Voltage on Signal Strength.

Results / Simulation / Discussion

The findings of this project provide a comprehensive validation of the plasma metasurface as a dynamic electromagnetic shield, bridging the gap between theoretical modeling and empirical performance.

1. Simulation Analysis (MATLAB Digital Twin):

•**Frequency-Dependent Threshold:** Simulation data (Figure 3) confirms that Shielding Effectiveness (SE) is a direct function of electron density (n_e).

•**Sensitivity to E-Field Intensity:** By modeling varying incident field intensities ($E_\circ 1$ to $E_\circ 4$), the results demonstrate that higher incident fields correlate with enhanced interaction energy, further validating the robustness of the **Drude Model** in predicting shield behavior.

Experimental Outcomes & Comparative Study:

•**Active vs. Passive Mitigation:** Experimental results (Chart 1) reveal a stark contrast between states. **Neon After Ionization** achieved superior attenuation compared to **Neon Before Ionization** and traditional passive materials like **Acrylic**.

•**Dynamic Range:** The system demonstrated an agile response across multiple testing categories, with ionized neon consistently providing the highest level of signal rejection, proving that a gas-based metasurface is more effective than static insulators.




Figure 3 Relationship between shielding efficiency and electron density

Conclusions

This research demonstrates the viability of an autonomous, plasma-based metasurface as a transformative solution for Electronic Protection (EP) in satellite communications. By integrating the physical properties of noble gas ionization with a closed-loop control framework, the system achieves a dynamic transition between transparency and high-performance shielding. Experimental and simulation results confirm that this software-defined response provides an agile, energy-efficient, and lightweight alternative to traditional static shielding, offering a robust defense mechanism for next-generation LEO satellite constellations in increasingly contested electromagnetic environments

ElectroSpace II Competition 2026

© Poster Template by Genigraphics® 1.800.790.4001 www.genigraphics.com